

Product properties			
Format		Floor Fields	New Classics
		2010 x 160 x 13 mm	1593 x 215 x 15 mm
Top layer		ca. 3.6 mm	
Packaging	Pack	9 Elements / 2.894 m ² / 19.395 kg	8 Elements / 2.74 m ² / 25.98 kg
	Pallet	32 Packs / 92.621 m ² / 620.640 kg	32 Packs / 87.679 m ² / 831.36 kg
Guarantee (according to Parador guarantee conditions)			25 years (domestic area)
Notes			- cleaning and maintenance see instructions - installation only by all-over adhesion - technical changes reserved
Product labelling			
     			
   			

*not valid for smoked products.

Tolerances (EN 13489)	
Admissible difference in length (± 0.1 %)	± 0.05 %
Admissible difference in width (± 0.2 mm)	± 0.1 mm
Squareness of the element (≤ 0.2 %)	≤ 0.05 %
Longitudinal curvature along the element (≤ 0.1 %)	≤ 0.05 %
Transverse curvature across the width (≤ 0.2 %)	≤ 0.08 %
Height differences of elements (≤ 0.2 mm)	≤ 0.18 mm
Moisture content at the time of first delivery (5-9%)	6 – 8 %

Classification general product features			
		Test method	Rating
	Resistance to roller castor chairs	EN 425	we recommend the use of a conventional chairmat
	Effect of a furniture leg	EN 424	No visible changes
	Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN ISO 10456	Floor Fields: 0.087 m ² *K/W New Classics: 0.100 m ² *K/W
	Formaldehyde (E1 = 0.1 ppm)	EN 717-1	≤ 0.05 ppm
	Acoustical - Impact noise reduction	ISO 717-2	18 dB (with Akustik-Protect 100)
	Disposal		EAK-Code-number 20 01 38

Classification surface characteristics			
		Test method	Rating
	Slip resistance	EN 13893	μ ≥ 0.49
		CEN/TS 15676	99 (USRV)
	Reaction to fire, click-installation as a floating floor	EN 13501-1	D _{fl} s1
	Reaction to fire, installation by all-over adhesion	EN 13501-1	D _{fl} s1
	Chemical resistance	EN 13442	Category 5 excepting ammonia solution (cat. 2)
	Bond strength / Cross cutting test	ISO 2409	n.n.
	Slip resistance, inclined plane	DIN 51130	R 10

Changed:	QMB	File name:	20190901_PA_TDS_Parkett_Edition_EN
Date:	01.08.2013	Latest update at:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.09.2019

Free sorting according to EN 13489		
Assortment:	Floor Fields	New Classics (french Herringbone pattern)
Characteristics according to EN 1310:	Upper side of the lamella	Upper side of the lamella
Type of wood:	Oak	
Botanical designation / Code (EN 13556):	Quercus petraea Liebl., Quercus robur L. / QCXE	
Shortcut / sorting / date (internal):	ES-LH-TT4-EI	ER-L-FGF-EI
	Version 12	Version 1
	2016	2013
	N2	N2
Sorting:	Select	Select
Sound sapwood	not permitted	not permitted
Knot (intergrown)	permitted: up to 15 mm	not permitted
Falling out knot	not permitted	not permitted
Pinkknots	permitted	permitted: up to 5 mm
Filling	permitted	permitted
Slight crack/ haircrack	not permitted	not permitted
Sugar inclusions, mineral inclusions	-	-
Bark pocket	not permitted	not permitted
Lightning cracks	permitted: in knots	not permitted
Slope of grain	no criterion	no criterion
Healthy heart	not permitted	-
Medullary ray	permitted	permitted
Discoloration, colour variation	permitted: slight colour variations	permitted: slight colour variations
White streaks	-	-
Pilling sticks marking	not permitted	not permitted
Biodeterioration (EN 1311)	not permitted	not permitted
Non-visible parts		
All features without restrictions to size or quantity permitted, provided they do not affect the strength or durability of the floor.		
Comment		
Maximum 3% of lamellas are allowed in the next lower grading. Wood is a natural product and therefore different in colour and texture. Samples, brochures and photos are therefore only approximate and not binding. The action of sunlight affects the natural variation in wood shade. This allows the product present at the time of delivery of significant differences to master.		

Changed:	QMB	File name:	20190901_PA_TDS_Parkett_Edition_Anhang_EN
Date:	01.08.2013	Update:	www.parador.eu/service/catalogues-downloads/technical-data-sheets
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.09.2019
			Page 1 of 1