

Product quality		
Format		1207 x 216 x 9,4 mm
Packaging	Pack:	7 elements / 1.825 m² / 17.00 kg
	Palette:	36 packs / 65.700 m² / 627.00 kg
Tolerances (requirement EN 16511)		
Squareness of the elements (≤ 0.20 mm)		≤ 0,20 mm/m
Determination of linearity (≤ 0.30 mm/m)		≤ 0,15 mm/m
Flatness concave / convex	lengthwise (≤ 0.50/≤ 1.0 %)	≤ 0,35 / ≤ 1,0 %
	wide (≤ 0.15/≤ 0.20 %)	≤ 0,10 / ≤ 0,10 %
Surface flushness	(average ≤ 0.10 mm)	average ≤ 0.10 mm
	(max. ≤ 0.15 mm)	max. ≤ 0.15 mm
Opening between installed elements	(average ≤ 0.15 mm)	average ≤ 0,05 mm
	(max. ≤ 0.20 mm)	max. ≤ 0.10 mm

Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (up to max. 20sqm)
Lifetime	10 years	- cleaning and maintenance see instructions
		- technical changes reserved
     		

Classification			
			
Utility class 23 = domestic areas with intensive use		Utility class 31 = commercial areas with low use	
The design floor meets all requirements of the designated utility class.			
Requirements / properties		Test method	Rating
	Wear layer	ISO 24340	0,3 mm
	Surface Coating		PUR
	Reaction to fire	EN 13501-1	B _{fl} s1
	Slip resistance	EN 13893	μ ≥ 0,35
		EN 14041	DS
	Staining resistance	EN 438-2	Category 1 + 2: level 4, slight change Category 3: level 3, moderate change
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN 425	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN ISO 10456	0,068 m²*K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
	Formaldehyde emission (E1 = 0.1 ppm)	EN 16516	≤ 0,05 ppm
	Acoustical - Impact noise reduction	ISO 717-2	15 dB (on Akustik-Protect 100) 16 dB (on PE film)
	Abrasion	prEN 15468 Annex A	≥ 1.500 rev.
	Impact resistance	EN 13329 Annex F	≥ 800 mm
	Thickness swelling	ISO 24336 (≤ 18%)	≤ 8%
	Water resistance	ISO 4760	Requirements met (72h instead of 24h)
	Antimicrobial activity	ISO 22196	Antibacterial
	Slip resistance on an inclined plane	EN 16165, Annex B	Brushed, wood texture: R9 / Vivid texture: R10
	Disposal	EAK-Code-number	17 02 03

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Selected_EN_20231001
Date:	01.06.2012	Latest update at:	www.parador.de/en/services/downloads/design-flooring
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.10.2023